

HDC enclosures HDC 48B SDLU 1PG29G

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com







The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Order No.	<u>1799810000</u>	
Туре	HDC 48B SDLU 1PG29G	
Version	HDC enclosures, Size: 12, Protection degree: IP 65, Base enclosure, End-locking clamp, lower side, Standard, with cover, Size of cable entries: PG 29	
GTIN (EAN)	4032248247035	
Qty.	1 pc(s).	



HDC enclosures HDC 48B SDLU 1PG29G

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Length	143 mm	Width	166.2 mm
Height	120 mm	Mounting dimension - width	111 mm
Mounting dimension - height	106 mm	Net weight	1,647 g

Dimensions

Total length housing	132 mm	Width housing C	90 mm
Width base C1	120 mm	Height of housing B	120 mm
Height of base B1	10 mm	Hole pitch length A2	111 mm
Cable entry	w. threading		

General data

Protection class note	Protection class with	Housing main material	
	secured cover: IP 65		diecast aluminium

Version

Design of housing	Base enclosure	Size	12
Design	Standard	Top part/bottom part/lid	lower part
Design of locking system	End-locking clamp, lower	Cable entry	
	side		w. threading
Size of cable entries	PG 29	Number of cable entry on top	0
Number of cable entry sideways	1	Cover	with cover

Classifications

ETIM 2.0	EC000437	ETIM 3.0	EC000437
UNSPSC	30-21-18-10	eClass 4.1	27-14-08-05
eClass 5.1	27-26-07-03	eClass 6.2	27-26-12-03
eClass 7.1	27-44-02-02		

Approvals

Approvals



ROHS Conform



HDC enclosures HDC 48B SDLU 1PG29G

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings

